

# Nghiên cứu, chế tạo hệ thống đóng cắt và giám sát thông số hệ thống điện dựa trên xử lý ảnh và IoT

## TÓM TẮT

Trong bài báo này chúng tôi đã đi vào nghiên cứu, chế tạo hệ thống đo lường, giám sát các thông số trong hệ thống điện dựa trên công nghệ IoT, và đóng cắt thiết bị trong phạm vi rộng dựa trên công nghệ xử lý ảnh để phát hiện đối tượng. Phần cứng của hệ thống được chế tạo với bộ thiết bị nhận diện đối tượng, UART PZEM-004T, esp32, Aptomat thông minh để thu thập các thông số dòng điện, điện áp, công suất, tần số, hệ số công suất, điện năng tiêu thụ và nhận diện đối tượng trong phạm vi giám sát. Các dữ liệu này sẽ được gửi lên server Node-Red chạy ở chế độ cục bộ hoặc Cloud thông qua giao thức Message Queuing Telemetry Transport (MQTT). Sau khi chế tạo hệ thống vận hành ổn định, có khả năng tự động đóng cắt thiết bị khi phát hiện đối tượng, người sử dụng có thể theo dõi trạng thái, điều khiển và cài đặt các thông số thông qua giao diện trên máy tính và điện thoại. Hệ thống còn có chức năng lưu trữ dữ liệu trên GoogleSheet, cảnh báo qua Email, điện thoại. Phần cứng của hệ thống được chế tạo với phần khung vỏ của các thiết bị đang có trên thị trường nên có khả năng ứng dụng cao trong thực tế.

**Từ khóa:** IoT, TensorFlow, Node-Red, hệ thống điện

Tiêu đề có các lỗi sai về ngữ pháp và ngữ nghĩa, tác giả nên đặt lại tiêu đề cho chuẩn hơn và đúng nghĩa theo nội dung của bài báo hơn

# Research and manufacture of switchgear systems and monitoring of electrical system parameters based on image processing and IoT

## ABSTRACTS

This paper **discusses** the development of a measurement and monitoring system for parameters in the power system that uses IoT technology. The system uses image processing technology and a range of object recognition devices to collect data on various parameters such as current, voltage, power, and **frequency**. The data collected is then sent to the Node-Red server using the MQTT protocol for further analysis. Once the system is operational, it can automatically switch off devices upon object detection. Users can monitor the system's status, control, and set parameters through an interface on their computer or phone. The system also can store data on Google and alert users via email or phone in case of any issues or anomalies. According to the paper, the hardware of the system has been designed using the shell of existing devices available in the market, making it highly applicable in real-life scenarios

**Keywords:** IoT, TensorFlow, Node-Red, Power-system

## 1. INTRODUCTION

It's fascinating to see how the industry is evolving with the 4.0 revolution, IoT technology, and AI. With the development of such technologies, we are witnessing the creation of more functional devices, particularly in electrical systems and sensors. Moreover, the servers being free for users and the introduction of embedded computers with small sizes and strong configurations like Raspberry Pi and Jesson Nano have made it easier for users to access IoT and AI.

 is gaining popularity in various fields such as industry, environment, and traffic monitoring<sup>1</sup>. In the electrical system, this technology is used to identify winding problems in transformers<sup>2</sup> and determine power quality<sup>3</sup>.

In Vietnam, the number of offices and public sector facilities is increasing rapidly. However, it can be challenging to save electricity in these areas based on user behavior, and current efforts are often inefficient<sup>4</sup>. With the rapid development of IoT technology, the application of smart switchgear such as switches and automats has partly solved the limitations in this area.

However, these devices often work with small currents, switching based on the control on

Động từ này không đủ mạnh cho bài báo khoa học

Các kết quả trong bài báo không có thể hiện dữ liệu về tần số???

Các lỗi về  
trích dẫn,  
về lỗi  
xuống  
hàng và ý  
nghĩa  
đoạn mờ  
đầu cần  
phải hiệu  
chỉnh

the phone or in combination with sensors such as motion sensors, and infrared sensors. Current devices are designed to either control or monitor electrical equipment, but they lack integration and the ability to detect people in large spaces such as classrooms or halls. Image processing technology has not been widely implemented in these devices to enable this functionality.


Based on the aforementioned issues, the author has conducted research and developed a system that includes functions such as wide-range image recognition for human detection to automatically switch electrical equipment. Additionally, the system can monitor, control, warn, and store data on parameters in the electrical system such as voltage, current, and power.

**2. CONTENTS** → Tên mục này không hợp lý -> Cần đặt lại

**2.1. IoT system** → IoT technology or IoT system???

IoT stands for the Internet of Things. A network of sensors, software, and other technologies that connect objects and devices, enabling them to collect and exchange data with each other<sup>5,6</sup>.

- Hình này chưa  
 được tham  
 chiếu  
 trong nội  
 dung bài  
 viết.  
 - Cần tăng  
 cỡ chữ  
 trong hình  
 lên từ 8pt  
 đến 10pt



**Figure 1.** The working principle of an IoT system

The Internet of Things (IoT) has vast application potential across all sectors. It's important to note that every complete IoT system encompasses four key steps: data collection, data sharing, data processing, and decision-making.

An IoT system typically comprises four main components: devices (Things), gateways (Gateways), network infrastructure (Network and Cloud), and analysis and data processing (Service and Solution Layers)<sup>7,8</sup>. These components work together to create a network of connected devices that can collect and exchange data with each other, enabling the creation of smart systems and applications.

Sensors within the research system measure electrical parameters, recognize objects, and convert them into data for the Internet. Users can easily process the signals and make necessary changes through phone or computer applications. Thùa


## 2.2. Image processing based on TensorFlow!

TensorFlow has indeed become the most popular deep-learning library in recent years. With TensorFlow, users have the flexibility to create various Deep Learning models such as convolutional Neural Networks (CNNs), Recurrent Neural Networks (RNNs), and artificial neural networks. It's a powerful tool that has transformed how we approach machine learning and data analysis.

TensorFlow is a powerful software library that enables numerical computations through data flow graphs. It is highly adaptable and can be used to program and train neural networks in multiple programming languages such as C, Java, and Python. Additionally, it allows for deploying applications on various platforms, including the cloud, machine local server, and mobile devices.

### 2.2.1. Core Elements in TensorFlow

TensorFlow is a library used for numerical computation and graphical representation of data that helps in creating and training machine learning models. These graphs consist of nodes and edges that represent calculations and corresponding data in the model. In general, the process of training a machine learning model in TensorFlow follows the steps shown in Figure 2.



**Figure 2.** Data flow chart for the training process.


In this training process, the user defines the computational graph structure by declaring variables and operations in the model. The processing is then defined to measure the difference between the model's predicted output and the actual value.

The data obtained after processing will be analyzed to determine the best parameter values that can minimize the loss function. The resulting values are then used to train and update the model. After the training, the model is tested with fresh data to assess its performance. Finally, the trained model is utilized to predict and categorize new data.

### 2.2.2. Application of TensorFlow library on Raspberry Pi

Raspberry is a computer that is designed to be compact and embedded, making it perfect for use in IoT projects. Suppose you want to object detection models. In that case, you can use TensorFlow Lite, which is a TensorFlow library that is specifically designed to work with Raspberry Pi 3 and Raspberry Pi 4 when they are running either Rasbian Buster or Rasbian Stretch. The process for installing and running this program on Raspberry is illustrated in Figure 3.

- Cần tăng  
 cỡ chữ  
 trong hình  
 lên từ 8pt  
 đến 10pt



**Figure 3.** TensorFlow installation procedure.

During the test, the results were displayed as depicted in Figure 4. To capture the camera frame, we used the OpenCV object. After capturing the frame, it was flipped horizontally and vertically for proper alignment and conversion to the required format that the model could process. The output of the model was a list of objects present in the frame, along with their corresponding parameters.




**Figure 4.** Object detection with TensorFlow Lite model.

The Object Detection model provides information on the location, class, and reliability of objects detected in a frame. To draw bounding boxes around an object, the model uses the coordinates of its upper-left and lower-right points. The layer's name is displayed with the bounding frame when a person is detected. Additionally, the class name is compared to a predefined label to determine its presence in the frame and the percentage match to the sample.

### 2.3. System Development Research

#### 2.3.1. System Design

The following study puts forward a system that is capable of monitoring the parameters in the electrical system and can be operated through object recognition within the observation field. It is combined with both local and remote control through the control interface which is depicted in Figure 5.



**Figure 5.** Schematic diagram of online monitoring structure for a distribution power system based on image processing and IoT.

The following are the primary stages of the system

A: Webcam and Raspberry Pi 4 are combined for image processing to monitor and detect people within its range.

B: The server and database are installed on the computer and run in the cloud.

C: Measurement and switching are carried out using Pzem - 004T and smart automatic TuyaA devices. These two measuring and switching devices are connected to Esp32 to transmit data to the server.

D: Monitor and control using your phone and computer.

The measurement and switching stage (C) involves using the PZEM-004T sensor to measure parameters such as voltage, current, frequency, power, power factor, and power consumption. These measurements are then uploaded to the server via ESP32. At the same time, the identification and image processing (A) system sends a signal to the server to detect the presence or absence of people within the field of view. The server is equipped with a monitoring and control interface and a control program for the data received from (A) and (C).

Vị trí này cần thêm bảng thể hiện các thông số kỹ thuật trong hệ thống thiết kế

Cấu trúc  
câu này  
không phù  
hợp với  
văn phong  
bài báo  
khoa học  
-> Cần  
phải viết  
lại.

The control signal is generated based on certain conditions such as the presence or absence of people in the field of view, overcurrent, and overvoltage. Data transmission between the stages is carried out using the MQTT protocol, and the microcontroller sends an automatic control signal to perform the power supply switching process.

### 2.3.2. Research and manufacture hardware

The system structure depicted in Figure 4 requires the installation and fabrication of hardware in two stages, namely (A) and (C). In the data recognition and processing stage (A), we make use of WebCam-PC-SWC-02 to connect to Raspberry Pi 4 Mode B. To observe the image processing, we employ a Waveshare 7-inch HDMI screen. Upon linking the devices, we obtain the results as depicted in Figure 6.



Figure 6. Installation of object recognition and handling equipment

To produce switchgear and measuring equipment, we carry out the following steps:

**Step 1.** To understand the structure and principle of the TuyA smart Aptomat with a rated current of 80A, you can conduct a test by simulating the control signals as shown in Figure 7. **This will help you identify the signal-receiving pins and connect them to the Esp32 using an intermediate relay.**



Figure 7. Construction and simulation of control circuit signals for switchgear

**Step 2.** To measure all parameters in the power system, we need to install a UART PZEM-004T measurement circuit with ESP32. This circuit is highly versatile and allows us to measure the electrical signal and voltage. The measurement pins are integrated with the **Atopmat** to measure the signal even when the

????

Figure 8




Figure 8. Installation of measuring equipment and switchgear

**Step 3.** Fabricate and install a smart switch using an existing mechanical switch, ESP32, and relay to control devices. Following the installation process, we will have a manual manipulator, which is depicted in Figure 9.




Figure 9. Renovate the mechanical switch.

## 2.4. Building a server for the system

### 2.4.1. Server and communication protocols

The system used to build the server involves Node-RED, a programming tool that enables the connection of hardware devices, APIs, and online services. It is primarily designed for IoT (Internet of Things) applications, but can also be used to quickly link different service flows for other applications. The construction of the data transmission scheme is illustrated in Figure 10.




Figure 10. Diagram of data transmission and reception in the system.

The Node-RED tools and software, database, and communication protocol will be installed on the server or cloud server. We will use influxDB and Google sheet to store system data, and all communication within the system will be done using MQTT communication. For this reason, we will install the Mosquitto broker on the server. The server will have an IP address which will serve as the host address to identify the object sending the monitoring state (publish) to the server. The measurement stage will publish the parameters in the power system to the server and, at the same time, receive data from the server through data registration (subscribe).

### 3. RESEARCH RESULTS

After fabrication, the devices are connected to form a complete system as depicted in Figure 11.



**Figure 11.** Actual results of the whole system.


After running the test, it was determined that the system operates stably and meets the requirements outlined in Figure 12.



**Figure 12.** Run a system test


The system can automatically switch electrical circuits based on signals from image recognition and processing on a Raspberry Pi. It also allows for local switching, remote access through Aptomat, as well as control through computers and phones. Additionally, users can monitor important electrical parameters such as voltage, current, and power consumption, which can help them evaluate their ability to save electricity while using the product.

The graph interface displays the parameters and stores them on the Google Sheet, as shown in Figure 13.14. This feature allows the user to monitor the switchgear status, the status of people being monitored, as well as the real-time values of voltage and current.



**Figure 13.** System monitoring interface

On the control interface, we can set threshold values for warnings and protection against overcurrent, over-voltage, and rising room temperature. The system has two levels of protection: warning and incident. If the alarm level exceeds the set threshold, the system will send an email and show a notification on the phone application, as shown in Figures 14 and 15. When the values surpass the alarm level, the system will send an email, show a notification on the phone, and activate the alarm.



**Figure 14.** Gmail and Google Sheet results

In addition to computer monitoring and control, the system also allows phone interface and function synchronization as shown in Figure 15.



**Figure 15.** Phone alerts, monitoring, and controls.

#### 4. CONCLUSION

Upon completion of the study, the system installation and inspection demonstrated stable performance that met the requirements. The devices utilized in the system are constructed on the chassis and shell of devices currently available in the market and utilized by consumers. As a result, the product is fully capable of being put into practical use and replacing existing devices.

The integration of image monitoring units via esp32-Cam image transmission to Raspberry Pi for image processing enhances monitoring scope and device control flexibility.

#### REFERENCES

1. PUTRA, Arman Syah; WARNERS, Harco Leslie Hendric Spits. Intelligent traffic monitoring system (ITMS) for smart cities based on IoT monitoring. In: 2018 Indonesian Association for Pattern Recognition International Conference (INAPR). *IEEE, 2018*. p. 161-165.
2. ALJOHANI, Omar; ABU-SIADA, Ahmed. Application of digital image processing to detect short-circuit turns in power transformers using frequency response analysis. *IEEE Transactions on Industrial Informatics, 2016*, 12.6: 2062-2073.
3. SHAREEF, Hussain; MOHAMED, Azah; IBRAHIM, Ahmad Asrul. An image processing-based method for power quality event identification. *International Journal of Electrical Power & Energy Systems, 2013*, 46: 184-197.
4. VAN HAO, Hoang. Officers' Electricity Saving in Open Offices: Exploring the Role of Perceived Behavior Control and Accessibility to Control. *2023*.
5. BEDI, Guneet; VENAYAGAMOORTHY, Ganesh Kumar; SINGH, Rajendra. Navigating the challenges of the Internet of Things (IoT) for power and energy systems. In: 2016 Clemson University Power Systems Conference (PSC). *IEEE, 2016*. p. 1-5.
6. AL-FUQAH, Ala, et al. Internet of Things: A survey on enabling technologies, protocols, and applications. *IEEE communications surveys & tutorials, 2015*, 17.4, 2347-2376.
7. KHAN, Rafiullah, et al. Future Internet: the Internet of Things architecture, possible applications, and key challenges. In: 2012 10th international conference on frontiers of information technology. *IEEE, 2012*. p. 257-260.
8. YANG, Zhihong, et al. Study and application of the architecture and key technologies for IoT. In: 2011 international conference on multimedia technology. *IEEE, 2011*. p. 747-751.
9. ERTAM, Fatih; AYDIN, Galip. Data classification with deep learning using TensorFlow. In: 2017 international conference on computer science and engineering (UBMK). *IEEE, 2017*. p. 755-758.
10. ABADI, Martín, et al. TensorFlow: a system for Large-Scale machine learning. *12th USENIX symposium on operating systems design and implementation (OSDI 16), 2016*. p. 265-283.



Cần bổ sung thêm vài tài liệu tham khảo công bố vào những năm gần đây. Ngoài ra, có thể thêm trích dẫn một số bài báo trên Tạp chí Khoa học Trường Đại học Quy Nhơn